

# EUROPEAN PARTS & ACCESSORIES

## Spray Lance - Dual (Karcher)

- ◆ 10.5 GPM flow rate
- ◆ 3600 PSI max. pressure
- ◆ 22 mm twist connect x 1/4" F
- ◆ 300° F
- ◆ Pure Pressure MTM dual lances



	Each
<b>J06-00148</b> Spray Lance, Dual - Vertical Knob - Zinc plated	<b>99.00</b>
<b>J06-00149</b> Spray Lance, Dual - Side Handle - Zinc plated	<b>101.90</b>

## Spray Lance (Karcher)

- ◆ 10.5 GPM flow rate
- ◆ 3600 PSI max. pressure
- ◆ M22x1.5 F swivel x M18M + OR
- ◆ 300° F
- ◆ Zinc plated tubing
- ◆ Vented
- ◆ Pure Pressure MTM lances



	Each
<b>J06-00145</b> Spray Lance - 35.5"	<b>52.75</b>
<b>J06-00146</b> Spray Lance - 59"	<b>66.40</b>
<b>J06-00147</b> Spray Lance - 79"	<b>76.85</b>

## Spray Tip Retainer (Karcher)

- ◆ M18x1 F threads
- ◆ Brass & plastic construction
- ◆ Pure Pressure MTM spray tip retainer



	Each
<b>J06-00150</b> Spray Tip Retainer	<b>4.20</b>

## Trigger Gun (Karcher)

- ◆ 10 GPM flow rate
- ◆ 4500 PSI max. pressure
- ◆ M22M 1 o-ring x M22M 2 o-ring
- ◆ 300° F
- ◆ Karcher direct replacement
- ◆ Pure Pressure MTM #Astra 320 series



	Each
<b>J06-00139</b> Trigger Gun	<b>51.40</b>
<b>J06-00140</b> Trigger Gun w/swivel	<b>52.00</b>

## Trigger Gun (Karcher)

- ◆ 7 GPM flow rate
- ◆ 3100 PSI max. pressure
- ◆ Ø 10 hose connection inlet
- ◆ 300° F
- ◆ Pure Pressure MTM #Aura 210/Ø10



		Each
<b>J06-00143</b>	Trigger Gun - 1/4" F outlet	<b>53.90</b>
<b>J06-00144</b>	Trigger Gun - M22M/2 o-ring outlet	<b>61.90</b>

## Trigger Gun (Karcher)

- ◆ 10 GPM flow rate
- ◆ 4100 PSI max. pressure
- ◆ M22M 1 o-ring x M22M 2 o-ring
- ◆ 300° F
- ◆ Karcher direct replacement
- ◆ Pure Pressure MTM #Iride 280



		Each
<b>J06-00141</b>	Trigger Gun	<b>42.25</b>
<b>J06-00142</b>	Trigger Gun w/swivel	<b>54.45</b>

## Trigger Gun (Karcher)

- ◆ 7 GPM flow rate
- ◆ 3100 PSI max. pressure
- ◆ M22M 1 o-ring x M22M 2 o-ring
- ◆ 300° F
- ◆ Karcher direct replacement
- ◆ Pure Pressure MTM #Aura 210



		Each
<b>J06-00138</b>	Trigger Gun	<b>45.90</b>

## General Pump's Twist Connects

- ◆ 10.5 GPM flow rate
- ◆ 4050 PSI max. pressure
- ◆ 320° F
- ◆ 1 O-ring, M22 (22mm)
- ◆ These twist disconnects couple U.S. pipe threads to European fittings.
- ◆ General's PA #YMIN series



		Each
<b>W05-14121-A</b>	Coupler - 1/4" MPT - #YMINB14M	<b>9.85</b>
<b>W05-14221-A</b>	Coupler - 1/4" FPT - #YMINB14F	<b>9.85</b>
<b>W05-14131-A</b>	Coupler - 3/8" MPT - #YMINB38M	<b>9.85</b>
<b>W05-14231-A</b>	Coupler - 3/8" FPT - #YMINB38F	<b>9.85</b>
<b>W05-14151-A</b>	Coupler - 1/2" MPT - #YMINB12M	<b>12.00</b>
<b>W05-14251-A</b>	Coupler - 1/2" FPT - #YMINB12F	<b>12.00</b>
<b>W05-14121-B</b>	Plug - 1/4" MPT - #YMINA14M	<b>3.70</b>
<b>W05-14221-B</b>	Plug - 1/4" FPT - #YMINA14F	<b>3.70</b>
<b>W05-14131-B</b>	Plug - 3/8" MPT - #YMINA38M	<b>3.70</b>
<b>W05-14231-B</b>	Plug - 3/8" FPT - #YMINA38F	<b>3.70</b>
<b>W05-14151-B</b>	Plug - 1/2" MPT - #YMINA12M	<b>4.10</b>
<b>W05-14251-B</b>	Plug - 1/2" FPT - #YMINA12F	<b>4.10</b>